

HYDRO EXTRACTOR LANA HE



The hydro extractor (centrifuge) LANA HE is perfectly suited for drying all kind of skins during the tanning process (capacity depends on model: approx. 40 - 155 kgs).

This top-discharge hydro extractors with drum filters are available in the drum dimensions 600 mms, 800 mms und 1200 mms. The extractors are useable for industrial purposes and huge quantities. The drums are placed on a very solid base frame with 3 pendulum columns (out of cast iron) which absorb the vibrations. The deep centre allows a compensation of an imbalanced load.

The machine is equipped with a mechanical brake.

All components which get in touch with moisture are out of stainless steel or anti rust treated steel. Solid construction, especially made for continuous working. The operation and handling of the machine is very easy and safe.

Technical data:

LANA

- Diameter 600 mms
 - inner cylinder size: 600x290 (diameter x height) mms
 - rotation speed: 1000 rpm
 - capacity: approx. 40 kgs
 - dimension: 1200x650 mms

- Diameter 800 mms
 - inner cylinder size: 800x350 (diameter x height) mms
 - rotation speed: 920 rpm
 - capacity: approx. 65kgs
 - dimension: 1400x700 mms

- Diameter 1200 mms
 - inner cylinder size: 1200x490 (diameter x height) mms
 - rotation speed: 740 rpm
 - capacity: approx. 155 kgs
 - dimension: 1950x950 mms